

L83(#)

Bill insertion	4 - way Acceptance
Acceptance speed	Approx. 1.5~3 seconds
Interface	L83: Pulse, ccTalk, RS-232, Parallel, CCNET, MDB, GBA L83#: Pulse, RS-232, CCNET, MDB, GBA
Bill Accepted Width	61~83 mm
Power Sources	L83: 12V DC (10.8~13.2V) L83#: 12V DC (10~16V)
Power consumption	Standby : 0.3A, 3.6W Operation : 1.2A, 14.4W Maximum : 2A, 24W
Environment range	Operating Temperature : L83: 0°C ~ 55°C / L83#: 0°C ~ 65°C Storage Temperature : -20° C ~ 70° C Humidity : 30%~85% RH (no condensation)
Weight	Approx. 800 g (shipping)
Acceptance rate	96% or more The second acceptance is included in the acceptance count. The following bills are excluded. a. Incomplete bills such as extremely dirty, wetted, broken or wrinkled ones. b. Bills folded at a corner or side. c. Incorrect-made bills.
Features	01.Fixed-width / Multi-width bill acceptable. 02.Multi-countries' currencies acceptable. 03.New generation design of verification system. 04.Anti-stringing technologies. 05.Ability of auto calibration. 06.Lightweight and durable plastic construction. 07.Speedy bill transaction 08.Selectable interfaces. 09.Multi-colored illumination bezel design. 10.Easy maintenance. 11.Fast program update.
Certificates	CE
Developed	Belarus, Bulgaria, China, Croatia, Czech, (Czech+Euro), Dominican, Euro, Poland, Romania, Slovakia, Switzerland, Ukraine, United Kingdom.

